



TEC-SPEC
FLO-TRACER™
Water Current Meter



Date: 05-04-2004

Rev.: 00

Page: Page 1 of 1



FLO-TRACER™

The Flo-Tracer™ is a hand held battery powered salt dilution open channel flowmeter for creeks, rivers and irrigation channels. The unit includes a IP65 enclosure with alphanumeric LCD display and a 4-key pad.

The Flo-Tracer™ can be set up using the key pad to answer the questions from the menu or using a PC with the Flo-Tracer™ windows software.

The LCD displays salinity, conductivity, temperature and flow rate in L/S
It is supplied complete with 10 m sensor cable (salinity range 0-2000 mg/l, 0-5000 mg/l with optional adaptor), Windows software, interface cable and carry case.

Parameters

Method: Salt dilution

Power Supply: 4 alkaline cells 1.5V type AAA, AM3, LR6, UM3, MIGNON

Battery life: Approx. 30hrs under normal conditions

Range of salinity gauging: zero to 2000 mg/l – extended to 5000 mg/l with adaptor

Response to salinity fluctuation: 0.1 mg/l

Precision of salinity gauging: +/- 1% max

Ratio (conductivity/salinity): 1.780 μ S/mg/l

Range of temperature measuring: zero to 40°C

Precision of temperature measuring: +/- 0.2°C

FLOW-TRONIC S.A. N.V.

Rue J.H. Cool 19a
B-4840 Welkenraedt
Belgium



Tel.: +32 (0)87 899797
Fax: +32 (0)87 899790
E-mail: sales@mmi-europe.com
Web: www.mmi-europe.com